## THORN

## 96268436 R2L2 S 24L35 WS 740 CL1




## R2L2

A small size LED road lighting lantern with 24 LEDs driven at 350mA with Wide Street optic. Electronic, fixed output control gear. Class I electrical, IP66, IK08. Housing: diecast aluminium, powder coated textured light grey. Diffuser: tempered flat glass. Screws: stainless steel, Ecolubric® treated. Post top (Ø60/76mm, tilted 0°/5°/10°) or lateral (Ø34/42/49/60mm, tilted 0°/-5°/-10°/-15°) mounting. Complete with 4000K LED.

Dimensions: 655 x 362 x 155 mm Total power: 28 W Weight: 9.54 kg Scx: 0.05 m<sup>2</sup>




TLG\_R2L2\_F\_SPDB.jpg



TLG\_R2L2\_M\_LDS.wmf

Lamp position: STD - standard Light Source: LED Luminaire luminous flux\*: 3280 lm Luminaire efficacy\*: 117 lm/W Lamp efficacy: 117 lm/W Colour Rendering Index min.: 70 LOR: 1,00 ULOR: 0,00 DLOR: 1,00



TLLA\_RS24L35WS4KG33\_DC.ldt

Correlated colour temperature\*: 4000 Kelvin Chromaticity tolerance (initial MacAdam)\*: 5 Rated median useful life\*: 100000h L90 at 25°C Ballast: 1x EL2 Luminaire input power\*: 28 W Lambda = 0.95 Dimming: TLD0

All values marked with an \* are rated values. Thorn uses tried and tested components from leading suppliers, however there may be isolated instances of technology-related failures of individual LEDs during the rated product lifetime. International standards set the tolerance in initial flux and connected load at  $\pm 10\%$ . Colour temperature is subject to a tolerance of up to +/-150 Kelvin from the nominal value. Unless stated otherwise, the values apply to an ambient temperature of  $25^{\circ}$ C.

In most products the failure of one LED point causes no functional impairment to the lighting performance of the luminaire and is therefore no reason for complaint. Unless otherwise stated all Thorn LED products are suitable for unrestricted use (rated RG0 or RG1) with regard photobiological blue light safety (IEC/EN60598-1).

Thorn Lighting is constantly developing and improving its products. The right is reserved to change specifications without prior notification or public announcement. © Thorn Lighting